SAFETY DATA SHEET

1. Identification

Ford

Motorcraft.

Product identifier	Rear View Mirror Adhesive	
Other means of identification		
FIR No.	196534	
Recommended use	Adhesive - activator	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/	Distributor information	
Company Name	Ford Motor Company	
Address	Attention: MSDS Information, P.O. Box 1899	
	Dearborn, Michigan 48121	
	USA	
Telephone	1-800-392-3673	
SDS Information	1-800-448-2063 (USA and Canada)	
	fordsds.com	
Emergency telephone numbers		
	Poison Control Center: USA and Canada: 1-8	00-959-3673
	INFOTRAC (Transportation): USA and Canac	la 1-800-535-5053
2. Hazard(s) identification		
Physical hazards	Flammable liquids	Category 2

Physical hazardsFlammable liquidsCategory 2Health hazardsSerious eye damage/eye irritationCategory 2Specific target organ toxicity, single exposureCategory 3 narcotic effectsEnvironmental hazardsHazardous to the aquatic environment, acute
hazardCategory 3Hazardous to the aquatic environment,
long-term hazardCategory 3

Not classified.



OSHA defined hazards

Signal word	Danger
Hazard statement	Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/eye protection/face protection.
Response	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. If skin irritation occurs: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. In case of fire: Use appropriate media to extinguish.
Storage	Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
PROPAN-2-OL		67-63-0	97 - 99
Copper Naphthenate		1338-02-9	1 - 2

Specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Avoid contact with eyes, skin, and clothing. Avoid breathing mist or vapor. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak. Keep unnecessary personnel away. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Local authorities should be advised if significant spillages cannot be contained. Wear appropriate protective equipment and clothing during clean-up. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.
	Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Avoid contact with eyes, skin, and clothing. Avoid breathing mist or vapor. Avoid prolonged exposure. When using do not smoke. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Take precautionary measures against static discharges. Explosion-proof general and local exhaust ventilation. Avoid release to the environment. Observe good industrial hygiene practices. Wear appropriate personal protective equipment. For personal protection, see section 8 of the SDS.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Туре	Value	
PEL	980 mg/m3	
	400 ppm	
6		
Туре	Value	Form
TWA	1 mg/m3	Dust and mist.
	0.2 mg/m3	Fume.
STEL	400 ppm	
TWA	200 ppm	
nical Hazards		
Туре	Value	Form
TWA	1 mg/m3	Dust and mist.
STEL	1225 mg/m3	
	500 ppm	
TWA	980 mg/m3	
	-	
	PEL s Type TWA STEL TWA nical Hazards Type TWA STEL	PEL 980 mg/m3 400 ppm s Type Value TWA 1 mg/m3 0.2 mg/m3 400 ppm TWA 2 mg/m3 Monopole 400 ppm TWA 2 mg/m3 TWA 200 ppm TWA 200 ppm TWA 1 mg/m3 STEL 1 mg/m3 STEL 1 225 mg/m3 STEL 500 ppm

Components	Value	Determinant	Specimen	Sampling Time
PROPAN-2-OL (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
* - For sampling details, p	lease see the sourc	e document.		
Appropriate engineering controls	exposure limit enclosure, ap	s/guidelines. If user ope	rations generate entilation, or oth	control airborne concentrations below the a vapor, dust and/or mist, use process er engineering controls to control airborne nes.
ndividual protection measu	res, such as perso	nal protective equipme	ent	
Eye/face protection	Wear safety g	lasses with side shields	(or goggles).	
Skin protection				
Hand protection	The choice of	an appropriate glove do	es not only depe	nen the potential exists for skin exposure. end on its material but also on other quality r. Nitrile gloves are recommended.
Other	Wear appropr	iate chemical resistant c	lothing if applica	ble.
Respiratory protection	protect worke maintenance	r health, an approved rea	spirator must be with the require	ntrations to a level which is adequate to worn. Respirator selection, use and ments of OSHA Respiratory Protection d CSA Z94.4.
Thermal hazards	Wear appropr	iate thermal protective c	lothing, when ne	cessary.
General hygiene considerations	after handling		eating, drinking,	onal hygiene measures, such as washing and/or smoking. Routinely wash work

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Liquid.
Color	Blue green.
Odor	Alcoholic.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	-129.1 °F (-89.5 °C)
Initial boiling point and boiling range	179.6 °F (82 °C)
Flash point	53.6 °F (12.0 °C)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or expl	losive limits
Explosive limit - lower (%)	2 %
Explosive limit - lower (%) Explosive limit - upper (%)	2 % 12 %
Explosive limit - upper (%)	12 %
Explosive limit - upper (%) Vapor pressure	12 % 43 hPa @ 20 degrees C
Explosive limit - upper (%) Vapor pressure Vapor density	12 % 43 hPa @ 20 degrees C Not available.
Explosive limit - upper (%) Vapor pressure Vapor density Relative density	12 % 43 hPa @ 20 degrees C Not available. 0.8
Explosive limit - upper (%) Vapor pressure Vapor density Relative density Relative density temperature	12 % 43 hPa @ 20 degrees C Not available. 0.8
Explosive limit - upper (%) Vapor pressure Vapor density Relative density Relative density temperature Solubility(ies) Solubility (water) Partition coefficient	12 % 43 hPa @ 20 degrees C Not available. 0.8 68 °F (20 °C)
Explosive limit - upper (%) Vapor pressure Vapor density Relative density Relative density temperature Solubility(ies) Solubility (water)	12 % 43 hPa @ 20 degrees C Not available. 0.8 68 °F (20 °C) 1 g/l @ 20 degrees C
Explosive limit - upper (%) Vapor pressure Vapor density Relative density Relative density temperature Solubility(ies) Solubility (water) Partition coefficient (n-octanol/water)	12 % 43 hPa @ 20 degrees C Not available. 0.8 68 °F (20 °C) 1 g/l @ 20 degrees C Not available.
Explosive limit - upper (%) Vapor pressure Vapor density Relative density Relative density temperature Solubility(ies) Solubility (water) Partition coefficient (n-octanol/water) Auto-ignition temperature	12 % 43 hPa @ 20 degrees C Not available. 0.8 68 °F (20 °C) 1 g/l @ 20 degrees C Not available. 797 °F (425 °C)

Other information VOC	98 % w/w
10. Stability and reactivity	,
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Isocyanates. Chlorine.
Hazardous decomposition products	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	May be irritating to the skin. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	May be harmful if swallowed.
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity

Causes serious eye irritation. May cause allergic skin reaction. May be irritating to the skin.

Components	Species	Calculated/Test Results
PROPAN-2-OL (CAS 67-63-0)		
Acute		
Dermal		
LD50	Rabbit	12800 mg/kg
Oral		
LD50	Dog	4797 mg/kg
	Mouse	3600 mg/kg
		4.5 g/kg
	Rabbit	6410 mg/kg
		8 g/kg
		5.03 g/kg
	Rat	5045 mg/kg
		4.7 g/kg
Other		
LD50	Mouse	4477 mg/kg
		1509 mg/kg
	Rat	2735 mg/kg
		1099 mg/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitizatio	n	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause sensitization by skin contact.	
FIR No.: 196534		SDS US

Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological information

Harmful to aquatic life with long lasting effects.

Ecotoxicity

Ecotoxicity

Components		Species	Calculated/Test Results	
PROPAN-2-OL (CAS 67-63-	-0)			
Aquatic				
Fish	LC50	Bluegill (Lepomis macrochirus)	> 1400 mg/l, 96 hours	
Persistence and degradability	No data is av	vailable on the degradability of this produ	ct.	
Bioaccumulative potential	No data avai	No data available.		
Mobility in soil	No data avai	No data available.		
Other adverse effects	The product potential.	The product contains volatile organic compounds which have a photochemical ozone creation potential.		

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

ΙΑΤΑ

UN number	UN1219
UN proper shipping name	Isopropanol
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	11
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo	Allowed with restrictions.
aircraft	
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number UN proper shipping name Transport hazard class(es)	UN1219 ISOPROPANOL (ISOPROPYL ALCOHOL)
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.

IATA; IMDG



15. Regulatory information

IS federal regulations	This product is a "Haz Standard, 29 CFR 19		efined by the OSHA Hazard Comn	nunicati
TSCA Section 12(b) Export	Notification (40 CFR 7	07, Subpt. D)		
Not regulated.				
CERCLA Hazardous Substa	ance List (40 CFR 302.4	4)		
Copper Naphthenate (CAS 1338-02-9)		Listed.		
PROPAN-2-OL (CAS 67		Listed.		
SARA 304 Emergency releated.	ise notification			
uperfund Amendments and R	eauthorization Act of 1	986 (SARA)		
Hazard categories Hazard categories Immediate Hazard Delayed Hazard - N Fire Hazard - Yes Pressure Hazard - Reactivity Hazard -		/es		
SARA 302 Extremely hazar	dous substance			
Not listed.				
SARA 311/312 Hazardous chemical	No			
SARA 313 (TRI reporting)				
Chemical name		CAS number	% by wt.	
Copper Naphthenate PROPAN-2-OL		1338-02-9 67-63-0	2.00000000000 99.00000000000	
Other federal regulations				
Clean Air Act (CAA) Section	n 112 Hazardous Air Po	ollutants (HAPs) List		
Not regulated.				
	n 112(r) Accidental Rel	ease Prevention (40 Cl	FR 68.130)	
Clean Air Act (CAA) Section				
Not regulated.				

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

PROPAN-2-OL (CAS 67-63-0)

International Inventories

All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

16. Other information, including date of preparation or last revision

Issue date	02-09-2017
Version	01
HMIS® ratings	Health: 1 Flammability: 3 Physical hazard: 0
NFPA ratings	Health: 1 Flammability: 3 Instability: 0
Preparation Information and Disclaimer	This document was prepared by FCSD-Toxicology, Ford Motor Company, Fairlane Business Park IV, 17225 Federal Drive, Allen Park, MI 48101, USA, based in part on information provided by the manufacturer. The information on this data sheet represents our current data and is accurate to the best of our knowledge as to the proper handling of this product under normal conditions and in accordance with the application specified on the packaging and/or technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user. To the extent that there are any differences between this product's Safety Data Sheet (SDS) and the consumer packaged product labels, the SDS should be followed.
Part number(s)	ТА-17-В