



SAFETY DATA SHEET

1. Identification

Product identifier Ultra Silicone Sealant

Other means of identification

FIR No. 174399

Recommended use Silicone sealant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier

Company Name Ford Motor Company
Address Attention: MSDS Information, P.O. Box 1899
Dearborn, Michigan 48121
USA
Telephone 1-800-392-3673
MSDS Information 1-800-448-2063
msds@brownart.com

Emergency telephone numbers

Poison Control Center: USA and Canada: 1-800-959-3673
INFOTRAC (Transportation): USA and Canada 1-800-535-5053

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 3

Hazardous to the aquatic environment, long-term hazard Category 3

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.

Signal word None.

Hazard statement Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Avoid release to the environment.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) May be harmful if swallowed. May cause irritation of respiratory tract. May irritate eyes and skin. When the product is exposed to moisture or during curing, 2-butanone oxime may be formed; this substance is toxic and irritates eyes and other mucous membranes.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
CALCIUM CARBONATE		471-34-1	20 - < 30
STEARIC ACID		57-11-4	3 - < 5
Butanone oxime		96-29-7	1 - < 3

Chemical name	Common name and synonyms	CAS number	%
ALUMINIUM		7429-90-5	< 1

Specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Do not induce vomiting. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Use water spray to cool unopened containers.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Avoid contact with eyes, skin, and clothing. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	This product is miscible in water. Stop the flow of material, if this is without risk. Prevent product from entering drains. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling	Provide adequate ventilation. Avoid contact with eyes, skin, and clothing. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
ALUMINIUM (CAS 7429-90-5)	PEL	5 mg/m ³	Respirable dust.
CALCIUM CARBONATE (CAS 471-34-1)	PEL	15 mg/m ³	Total dust.
		5 mg/m ³	Respirable fraction.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
		15 mg/m3	Total dust.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
ALUMINIUM (CAS 7429-90-5)	TWA	1 mg/m3	Respirable fraction.
STEARIC ACID (CAS 57-11-4)	TWA	10 mg/m3	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
ALUMINIUM (CAS 7429-90-5)	TWA	5 mg/m3	Respirable.
		5 mg/m3	Welding fume or pyrophoric powder.
		10 mg/m3	Total
CALCIUM CARBONATE (CAS 471-34-1)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
Butanone oxime (CAS 96-29-7)	TWA	36 mg/m3
		10 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Occupational Exposure Limits are not relevant to the current physical form of the product.

Appropriate engineering controls

Use adequate ventilation to control airborne concentrations below the exposure limits/guidelines. If user operations generate a vapor, dust and/or mist, use process enclosure, local exhaust ventilation, or other engineering controls to control airborne levels below the recommended exposure limits/guidelines.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear safety glasses with side shields (or goggles).

Skin protection**Hand protection**

Suitable chemical protective gloves should be worn when the potential exists for prolonged or repeated skin exposure. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Neoprene gloves are recommended. Nitrile gloves are recommended.

Other

Wear suitable protective clothing. Wear appropriate chemical resistant clothing if applicable.

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard 29 CFR 1910.134 and/or Canadian Standard CSA Z94.4.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance****Physical state**

Solid.

Form

Paste.

Color

Grey.

Odor

Mild.

Odor threshold

Not available.

pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	203.0 °F (95.0 °C) ASTM D56
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	< 5 mm Hg
Vapor pressure temp.	69.8 °F (21 °C)
Vapor density	> 1 (AIR=1)
Relative density	1.47
Relative density temperature	39.2 °F (4 °C)
Solubility(ies)	
Solubility (water)	POLYMERIZES
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
VOC (Weight %)	< 2 % CAM310

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Fluorine. Strong oxidizing agents. Water.
Hazardous decomposition products	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Nitrogen oxides (NOx). Formaldehyde.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause irritation to the respiratory system.
Skin contact	May be irritating to the skin.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components	Species	Calculated/Test Results
CALCIUM CARBONATE (CAS 471-34-1)		
Acute		
<i>Oral</i>		
LD50	Mouse	6450 mg/kg
	Rat	6450 mg/kg
STEARIC ACID (CAS 57-11-4)		
Acute		
<i>Oral</i>		
LD50	Rat	4.6 g/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
Not listed.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
12. Ecological information		
Ecotoxicity	Harmful to aquatic life with long lasting effects.	
Ecotoxicity		
Components	Species	Calculated/Test Results
ALUMINIUM (CAS 7429-90-5)		
Aquatic		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 0.16 mg/l, 96 hours
Butanone oxime (CAS 96-29-7)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 777 - 914 mg/l, 96 hours
CALCIUM CARBONATE (CAS 471-34-1)		
Aquatic		
Fish	LC50	Western mosquitofish (Gambusia affinis) > 56000 mg/l, 96 hours
Persistence and degradability	No data is available on the degradability of this product.	
Bioaccumulative potential		
Partition coefficient n-octanol / water (log Kow)		
STEARIC ACID		8.23
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT	
<Unspecified>	Not regulated as dangerous goods.
IATA	
<Unspecified>	Not regulated as dangerous goods.
IMDG	
<Unspecified>	Not regulated as dangerous goods.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.		
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	Not regulated.		
CERCLA Hazardous Substance List (40 CFR 302.4)	Not listed.		
SARA 304 Emergency release notification	Not regulated.		
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	Not listed.		
Superfund Amendments and Reauthorization Act of 1986 (SARA)			
Hazard categories	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No		
SARA 302 Extremely hazardous substance	Not listed.		
SARA 311/312 Hazardous chemical	No		
SARA 313 (TRI reporting)			
Chemical name	CAS number	% by wt.	
ALUMINIUM	7429-90-5	< 1	
Other federal regulations			
Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List	Not regulated.		

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

ALUMINIUM (CAS 7429-90-5)
CALCIUM CARBONATE (CAS 471-34-1)

US. New Jersey Worker and Community Right-to-Know Act

ALUMINIUM (CAS 7429-90-5)
CALCIUM CARBONATE (CAS 471-34-1)

US. Pennsylvania Worker and Community Right-to-Know Law

ALUMINIUM (CAS 7429-90-5)
CALCIUM CARBONATE (CAS 471-34-1)

US. Rhode Island RTK

ALUMINIUM (CAS 7429-90-5)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

16. Other information, including date of preparation or last revision

Issue date 05-14-2015

Version # 01

HMIS® ratings Health: 1
Flammability: 1
Physical hazard: 0

NFPA ratings Health: 1
Flammability: 1
Instability: 0

Preparation Information and Disclaimer This document was prepared by FCSD-Toxicology, Ford Motor Company, Diagnostic Service Center II, 1800 Fairlane Drive, Allen Park, MI 48101, USA, based in part on information provided by the manufacturer. The information on this data sheet represents our current data and is accurate to the best of our knowledge as to the proper handling of this product under normal conditions and in accordance with the application specified on the packaging and/or technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user. To the extent that there are any differences between this product's Safety Data Sheet (SDS) and the consumer packaged product labels, the SDS should be followed.

Part number(s) TA-29