

**Motorcraft**

FICHA TÉCNICA

MOTORCRAFT SAE 10W-30 Super Duty Diesel Motor Oil

FICHA TÉCNICA - Motorcraft SAE 10W-30 Super Duty Motor Oil. Aceite para motores a Diesel.

DESCRIPTION

Motorcraft® SAE 10W-30 Super Duty Diesel Motor Oil is a high-quality light- and heavy-duty diesel engine oil recommended by Ford Motor Company. It is particularly recommended for use in Ford vehicles equipped with Power Stroke® Diesel engines, as well as in other diesel engine applications where the manufacturer recommends an oil of this viscosity grade and quality. It meets Ford WSS-M2C171-F1, required for use in Power Stroke® Diesel engines designed to meet 2017 on-highway exhaust emission standards and requiring ultralow sulfur diesel fuel as well as meeting the requirements for previous model year diesel engines.

Motorcraft® SAE 10W-30 Super Duty Diesel Motor Oil is a high-quality diesel engine oil formulated with premium hydroprocessed base oils and unique additive technology. It satisfies the warranty requirements of Ford Motor Company, as well as most other domestic and import diesel engine manufacturers. It meets the requirements of Cummins CES 20086, Detroit Diesel 93K222, Volvo VDS-4.5, Mack EOS-4.5 and API Service CK-4.

Motorcraft® SAE 10W-30 Super Duty Diesel Motor Oil is formulated for improved oxidation protection and contains more than 1000 ppm phosphorus to improve wear protection. Designed for low emission diesel engines providing excellent soot control, protection against wear, deposits, rust and corrosion, foaming, sludge formation, high temperature oxidation and thickening, as well as protecting exhaust aftertreatment systems such as particulate filters. It also provides excellent performance in older-generation diesel engines operating on high-sulfur fuel.

Motorcraft® SAE 10W-30 Super Duty Diesel Motor Oil is recommended for use in 7.3L, 6.4L and 6.0L Powerstroke® diesel engines from 0 °F (-18 °C) to 50 °F (10 °C) and 6.7L Powerstroke® diesel engines above 0 °F (-18 °C)

°Do not use in gasoline engines equipped with catalysts

**Motorcraft.**

FICHA TÉCNICA

MOTORCRAFT SAE 10W-30 Super Duty Diesel Motor Oil

FICHA TÉCNICA - Motorcraft SAE 10W-30 Super Duty Motor Oil. Aceite para motores a Diesel.

PRODUCT TYPICALS

Motorcraft® SAE 10W-30 Super Duty Diesel Motor Oil

SAE Grade	10W-30
Specific Gravity @ 60°F(15.6°C)	0.867
Density, lb/gal	7.25
Flash Point, COC, °C (°F)	277 (441)
Viscosity:	
cSt @100°C	11.8
cSt @40°C	78.9
cP @-25°C	6000
Viscosity Index	146
Pour Point, °C (°F)	<-42 (<-44)
Total Base Number	9.6
Phosphorus Content	1060ppm

Detailed physical, health, and safety information on this product is available on a Safety Data Sheet. This SDS form may be obtained by writing or calling Ford Motor Company, P.O. Box 1899, Attention SDS, Dearborn, MI 48121. Phone: (800) 448-2063. Fax: (800) 466-3753

To continue to provide superior quality, Motorcraft reserves the right to change the composition of its products without notice.

MOTORCRAFT.COM/MX