## FICHA TÉCNICA - Motorcraft SAE 0W-20 Full Synthetic Motor Oil. Aceite para motores a gasolina.

## DESCRIPTION

**Motorcraft® SAE 0W-20 Full Synthetic Motor Oil** is a premium-quality passenger car motor oil recommended by Ford Motor Company and meets all warranty requirements. It is API Certified for gasoline engine service ILSAC GF-6 and meets API SP/Resource Conserving and SN PLUS.

**Motorcraft® SAE 0W-20 Full Synthetic Motor Oil** is manufactured with high-viscosity index, premiumquality, synthetic base oils that provide good high temperature and low temperature performance. It helps minimize engine deposits and wear, protect against high-temperature oxidation and turbocharger desposits, low-temperature gelling, rust corrosion and foaming. The friction-reducing technology in this motor oil provides superior wear protection and energy-conserving characteristics, which result in significant improvement in fuel economy when compared to SAE 5W-30 motor oils. This oil also meets WSS-M2C962-A1 and reduces oil derived low speed pre-ignition.

Motorcraft® SAE 0W-20 Full Synthetic Motor Oil is also formulated to meet General Motors vehicles' maintenance needs.

## PRODUCT TYPICALS

Motorcraft® SAE 0W-20 Full Synthetic Motor Oil	
SAE Grade	0W-20
Ford Material Specification	WSS-M2C962-A1
API Service	GF-6/SP/RC/SN PLUS
Specific Gravity @ 60°F(15.6°C)	0.846
Density, lb/gal	7.04
Flash Point, COC, °C (°F)	226 (439)
Viscosity:	
cSt @100°C	8.5
cSt @40°C	45
cP @-35°C	5550
Viscosity Index	169
Pour Point,°C (°F)	<-50 (<-58)

Detailed physical, health, and safety information on this product is available on a Safety Data Sheet. This SDS form may be obtained by writing or calling Ford Motor Company, Attention: SDS, P.O. Box 1899, Dearborn, MI 48121.

Phone: (800) 448-2063; www.fordsds.com

To continue to provide superior quality, Motorcraft reserves the right to change the composition of its products without notice.