



FICHA TÉCNICA

MOTORCRAFT SAE 5W-20 Full Synthetic Motor Oil

FICHA TÉCNICA - Motorcraft SAE 5W-20 Full Synthetic Motor Oil. Aceite para motores a gasolina.

DESCRIPTION

Motorcraft® SAE 5W-20 Full Synthetic Motor Oil is a premium-quality passenger car motor oil recommended by Ford Motor Company and meets all warranty requirements. It is API Certified for gasoline engine service ILSAC GF-6 and meets API SP/Resource Conserving and SN PLUS.

Motorcraft® SAE 5W-20 Full Synthetic Motor Oil is manufactured with high-viscosity index, premium-quality, synthetic base oils that provide good high temperature and low temperature performance. It provides improved protection against engine wear, and deposits, oil thickening and oil derived low speed pre-ignition, while continuing to prevent turbocharger deposits, low-temperature gelling, rust corrosion and foaming. The friction-reducing technology in this motor oil provides superior wear protection and energy-conserving characteristics, which result in significant improvement in fuel economy when compared to SAE 5W-30 and 10W-30 motor oils. This oil also meets WSS-M2C960-A1.

PRODUCT TYPICALS

Motorcraft® SAE 5W-20 Full Synthetic Motor Oil	
SAE Grade	5W-20
Ford Material Specification	WSS-M2C960-A1
API Service	GF-6/SP/RC/SN PLUS
Specific Gravity @ 60°F(15.6°C)	0.848
Density, lb/gal	7.06
Flash Point, COC, °C (°F)	229 (444)
Viscosity:	
cSt @100°C	8.7
cSt @40°C	44
cP @-30°C	4500
Viscosity Index	166
Pour Point, °C (°F)	<-40 (<-40)

Detailed physical, health, and safety information on this product is available on a Safety Data Sheet. This SDS form may be obtained by writing or calling Ford Motor Company, Attention: SDS, P.O. Box 1899, Dearborn, MI 48121.
Phone: (800) 448-2063; www.fordsds.com

To continue to provide superior quality, Motorcraft reserves the right to change the composition of its products without notice.