



FICHA TÉCNICA

MOTORCRAFT SAE 5W-50 Full Synthetic Motor Oil

FICHA TÉCNICA - Motorcraft SAE 5W-50 Full Synthetic Motor Oil. Aceite para motores a gasolina.

DESCRIPTION

Motorcraft® SAE 5W-50 Full Synthetic Motor Oil is recommended by Ford Motor Company for use in the Ford GT, Shelby GT-500, GT-350, Boss 302, Focus RS and Ford GT Supercar.

Motorcraft® SAE 5W-50 Full Synthetic Motor Oil is manufactured with high viscosity index, premium-quality synthetic base oils and performance additives to provide wear and oxidation protection under severe operating conditions. It is resistant to deposit formation, including supercharged and turbocharged applications. It provides quick flow to engine parts during start-up and lubricates effectively over a wide temperature range.

This oil is compatible with other synthetic and petroleum-based formulations.

PRODUCT TYPICALS

Motorcraft® SAE 5W-50 Full Synthetic Motor Oil	
SAE Grade	5W-50
API Service	SN
Specific Gravity @ 60°F(15.6°C)	0.865
Density, lb/gal	7.20
Flash Point, COC, °C (°F)	229 (444)
Viscosity:	
cSt @100°C	21.0
cSt @40°C	136
cP @-30°C	5900
Viscosity Index	181
Pour Point, °C (°F)	<-42 (<-44)

Detailed physical, health, and safety information on this product is available on a (Material) Safety Data Sheet. This (M)SDS form may be obtained by writing or calling Ford Motor Company, P.O. Box 1899, Attention MSDS, Dearborn, MI 48121.
Phone: (712) 826-3752. Fax: (800) 466-3753.

To continue to provide superior quality, Motorcraft reserves the right to change the composition of its products without notice.