

1. Identification**Product identifier** Metal Brake Parts Cleaner- High VOC**Other means of identification****FIR No.** 191860**Recommended use** Metal brake parts cleaner**Recommended restrictions** None known.**Manufacturer/Importer/Supplier/Distributor information****Supplier**

Company Name Ford Motor Company
Address Attention: MSDS Information, P.O. Box 1899
Dearborn, Michigan 48121
USA
Telephone 1-800-392-3673
MSDS Information 1-800-448-2063
msds@brownart.com

Emergency telephone numbers

Poison Control Center: USA and Canada: 1-800-959-3673
INFOTRAC (Transportation): USA and Canada 1-800-535-5053

2. Hazard(s) identification

| | | |
|------------------------------|--|-------------|
| Physical hazards | Flammable liquids | Category 1 |
| Health hazards | Acute toxicity, oral | Category 4 |
| | Carcinogenicity | Category 2 |
| | Reproductive toxicity | Category 1B |
| | Specific target organ toxicity, single exposure | Category 1 |
| | Aspiration hazard | Category 1 |
| Environmental hazards | Hazardous to the aquatic environment, acute hazard | Category 2 |
| | Hazardous to the aquatic environment, long-term hazard | Category 2 |
| OSHA defined hazards | Not classified. | |

Label elements**Signal word** Danger**Hazard statement** Extremely flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Suspected of causing cancer. May damage fertility or the unborn child. Causes damage to organs. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.**Precautionary statement****Prevention**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

| | |
|--|---|
| Response | If swallowed: Immediately call a poison center/doctor. Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If exposed: Call a poison center/doctor. If exposed or concerned: Get medical advice/attention. In case of fire: Use appropriate media to extinguish. Collect spillage. |
| Storage | Store in a well-ventilated place. Keep cool. Store locked up. |
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Hazard(s) not otherwise classified (HNOC) | Aspiration may cause pulmonary edema and pneumonitis. Irritating to eyes, respiratory system and skin. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May be fatal or cause blindness if swallowed. Cannot be made nonpoisonous. |
| Supplemental information | None. |

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|---------------|--------------------------|------------|-----------|
| XYLENE | | 1330-20-7 | 50 - < 60 |
| METHANOL | | 67-56-1 | 30 - < 40 |
| ETHYLBENZENE | | 100-41-4 | 10 - < 20 |
| TOLUENE | | 108-88-3 | < 1 |

Specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

| | |
|---|--|
| Inhalation | Move to fresh air. Call a physician if symptoms develop or persist. |
| Skin contact | Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists. |
| Eye contact | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists. |
| Ingestion | Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. |
| Most important symptoms/effects, acute and delayed | Dizziness. Headache. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause temporary irritation. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed. |
| General information | Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse. |

5. Fire-fighting measures

| | |
|--|--|
| Suitable extinguishing media | Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2). |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. |
| Special protective equipment and precautions for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| Fire fighting equipment/instructions | In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. |
| General fire hazards | Extremely flammable liquid and vapor. |

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid contact with eyes. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Do not breathe mist or vapor. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value |
|-----------------------------|------|----------------------------------|
| ETHYLBENZENE (CAS 100-41-4) | PEL | 435 mg/m ³ 100 ppm |
| METHANOL (CAS 67-56-1) | PEL | 260 mg/m ³ 200 ppm |
| XYLENE (CAS 1330-20-7) | PEL | 435 mg/m ³ 100 ppm |

US. OSHA Table Z-2 (29 CFR 1910.1000)

| Components | Type | Value |
|------------------------|----------------|--------------------|
| TOLUENE (CAS 108-88-3) | Ceiling TWA | 300 ppm 200 ppm |

US. ACGIH Threshold Limit Values

| Components | Type | Value |
|-----------------------------|------|---------|
| ETHYLBENZENE (CAS 100-41-4) | TWA | 20 ppm |
| METHANOL (CAS 67-56-1) | STEL | 250 ppm |

US. ACGIH Threshold Limit Values

| Components | Type | Value |
|------------------------|------|---------|
| | TWA | 200 ppm |
| TOLUENE (CAS 108-88-3) | TWA | 20 ppm |
| XYLENE (CAS 1330-20-7) | STEL | 150 ppm |
| | TWA | 100 ppm |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value |
|-----------------------------|------|-----------|
| ETHYLBENZENE (CAS 100-41-4) | STEL | 545 mg/m3 |
| | | 125 ppm |
| | TWA | 435 mg/m3 |
| | | 100 ppm |
| METHANOL (CAS 67-56-1) | STEL | 325 mg/m3 |
| | | 250 ppm |
| | TWA | 260 mg/m3 |
| | | 200 ppm |
| TOLUENE (CAS 108-88-3) | STEL | 560 mg/m3 |
| | | 150 ppm |
| | TWA | 375 mg/m3 |
| | | 100 ppm |

Biological limit values**ACGIH Biological Exposure Indices**

| Components | Value | Determinant | Specimen | Sampling Time |
|-----------------------------|-----------|---|---------------------|---------------|
| ETHYLBENZENE (CAS 100-41-4) | 0.15 g/g | Sum of mandelic acid and phenylglyoxylic acid | Creatinine in urine | * |
| METHANOL (CAS 67-56-1) | 15 mg/l | Methanol | Urine | * |
| TOLUENE (CAS 108-88-3) | 0.3 mg/g | o-Cresol, with hydrolysis | Creatinine in urine | * |
| | 0.03 mg/l | Toluene | Urine | * |
| | 0.02 mg/l | Toluene | Blood | * |
| XYLENE (CAS 1330-20-7) | 1.5 g/g | Methylhippuric acids | Creatinine in urine | * |

* - For sampling details, please see the source document.

Exposure guidelines**US - California OELs: Skin designation**

METHANOL (CAS 67-56-1) Can be absorbed through the skin.
TOLUENE (CAS 108-88-3) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

METHANOL (CAS 67-56-1) Skin designation applies.
TOLUENE (CAS 108-88-3) Skin designation applies.

US - Tennessee OELs: Skin designation

METHANOL (CAS 67-56-1) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

METHANOL (CAS 67-56-1) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

METHANOL (CAS 67-56-1) Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Eye wash fountain and emergency showers are recommended. Use adequate ventilation to control airborne concentrations below the exposure limits/guidelines. If user operations generate a vapor, dust and/or mist, use process enclosure, local exhaust ventilation, or other engineering controls to control airborne levels below the recommended exposure limits/guidelines.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

| | |
|---------------------------------------|---|
| Skin protection | |
| Hand protection | Suitable chemical protective gloves should be worn when the potential exists for prolonged or repeated skin exposure. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Viton gloves are recommended. |
| Other | Wear suitable protective clothing. Wear appropriate chemical resistant clothing if applicable. |
| Respiratory protection | If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard 29 CFR 1910.134 and/or Canadian Standard CSA Z94.4. |
| Thermal hazards | Wear appropriate thermal protective clothing, when necessary. |
| General hygiene considerations | Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. |

9. Physical and chemical properties

Appearance

| | |
|---|----------------------------|
| Physical state | Liquid. |
| Form | Liquid. |
| Color | Colorless. |
| Odor | Alcoholic. |
| Odor threshold | Not available. |
| pH | Not available. |
| Melting point/freezing point | Not available. |
| Initial boiling point and boiling range | Not available. |
| Flash point | 52.0 °F (11.1 °C) ASTM D56 |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not applicable. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | Not available. |
| Flammability limit - upper (%) | Not available. |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | Not available. |
| Vapor density | Not available. |
| Relative density | 0.8 - 0.9 |
| Relative density temperature | 77 °F (25 °C) |
| Solubility(ies) | |
| Solubility (water) | SLIGHT IN WATER |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | Not available. |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Kinematic viscosity | < 15 cSt |
| Kinematic viscosity temperature | 104 °F (40 °C) |

VOC (Weight %) 10 % w/w CAM310

10. Stability and reactivity

| | |
|---|--|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | Hazardous polymerization does not occur. |
| Conditions to avoid | Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| Incompatible materials | Strong acids. Strong oxidizing agents. Halogens. |
| Hazardous decomposition products | Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. |

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause damage to organs by inhalation. May cause irritation to the respiratory system. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful.

Skin contact Harmful if absorbed through skin.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. May be fatal or cause blindness if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Headache. Dizziness. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

| Components | Species | Calculated/Test Results |
|-----------------------------|---------|--|
| ETHYLBENZENE (CAS 100-41-4) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | 17800 mg/kg |
| <i>Oral</i> | | |
| LD50 | Rat | 3500 mg/kg |
| METHANOL (CAS 67-56-1) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | 15800 mg/kg |
| <i>Inhalation</i> | | |
| LC50 | Cat | 85.41 mg/l, 4.5 Hours 43.68 mg/l, 6 Hours |
| | Rat | 64000 ppm, 4 Hours 87.5 mg/l, 6 Hours |
| <i>Oral</i> | | |
| LD50 | Dog | 8000 mg/kg |
| | Monkey | 2 g/kg |
| | Mouse | 7300 mg/kg |
| | Rabbit | 14.4 g/kg |
| | Rat | 5628 mg/kg |

| Components | Species | Calculated/Test Results |
|---|---|---|
| TOLUENE (CAS 108-88-3) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | 12124 mg/kg 14.1 ml/kg |
| <i>Inhalation</i> | | |
| LC50 | Mouse | 5320 ppm, 8 Hours 400 ppm, 24 Hours |
| | Rat | 26700 ppm, 1 Hours 12200 ppm, 2 Hours 8000 ppm, 4 Hours |
| <i>Oral</i> | | |
| LD50 | Rat | 2.6 g/kg |
| XYLENE (CAS 1330-20-7) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | > 43 g/kg |
| <i>Inhalation</i> | | |
| LC50 | Mouse | 3907 mg/l, 6 Hours |
| | Rat | 6350 mg/l, 4 Hours |
| <i>Oral</i> | | |
| LD50 | Mouse | 1590 mg/kg |
| | Rat | 3523 - 8600 mg/kg |
| Skin corrosion/irritation | Prolonged skin contact may cause temporary irritation. | |
| Serious eye damage/eye irritation | Direct contact with eyes may cause temporary irritation. | |
| Respiratory or skin sensitization | | |
| Respiratory sensitization | Not a respiratory sensitizer. | |
| Skin sensitization | This product is not expected to cause skin sensitization. | |
| Germ cell mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. | |
| Carcinogenicity | Suspected of causing cancer. | |
| IARC Monographs. Overall Evaluation of Carcinogenicity | | |
| ETHYLBENZENE (CAS 100-41-4) | 2B Possibly carcinogenic to humans. | |
| TOLUENE (CAS 108-88-3) | 3 Not classifiable as to carcinogenicity to humans. | |
| XYLENE (CAS 1330-20-7) | 3 Not classifiable as to carcinogenicity to humans. | |
| OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) | | |
| Not listed. | | |
| Reproductive toxicity | Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. May damage fertility or the unborn child. | |
| Specific target organ toxicity - single exposure | Causes damage to organs. Central nervous system. Liver. Optic nerves. | |
| Specific target organ toxicity - repeated exposure | Not classified. | |
| Aspiration hazard | May be fatal if swallowed and enters airways. | |
| Chronic effects | Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. | |
| 12. Ecological information | | |
| Ecotoxicity | Toxic to aquatic life with long lasting effects. | |

Ecotoxicity

| Components | | Species | Calculated/Test Results |
|-----------------------------|------|--|------------------------------|
| ETHYLBENZENE (CAS 100-41-4) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 1.37 - 4.4 mg/l, 48 hours |
| Fish | LC50 | Fathead minnow (Pimephales promelas) | 7.5 - 11 mg/l, 96 hours |
| METHANOL (CAS 67-56-1) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | > 10000 mg/l, 48 hours |
| Fish | LC50 | Fathead minnow (Pimephales promelas) | > 100 mg/l, 96 hours |
| TOLUENE (CAS 108-88-3) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 5.46 - 9.83 mg/l, 48 hours |
| Fish | LC50 | Coho salmon, silver salmon (Oncorhynchus kisutch) | 8.11 mg/l, 96 hours |
| XYLENE (CAS 1330-20-7) | | | |
| Aquatic | | | |
| Fish | LC50 | Bluegill (Lepomis macrochirus) | 7.711 - 9.591 mg/l, 96 hours |

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

| | |
|--------------|------------|
| ETHYLBENZENE | 3.15 |
| METHANOL | -0.77 |
| TOLUENE | 2.73 |
| XYLENE | 3.12 - 3.2 |

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

| | |
|--|--|
| Disposal instructions | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Local disposal regulations | Dispose in accordance with all applicable regulations. |
| Hazardous waste code | The waste code should be assigned in discussion between the user, the producer and the waste disposal company. |
| Waste from residues / unused products | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). |
| Contaminated packaging | Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. |

14. Transport information

DOT

<Unspecified>

| | |
|-------------------------------------|---|
| UN number | UN1993 |
| UN proper shipping name | FLAMMABLE LIQUIDS, N.O.S. (METHYL ALCOHOL, XYLENE (ALL ISOMERS)) |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Label(s) | 3 |
| Packing group | II |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |

IATA

<Unspecified>

| | |
|------------------------------|---|
| UN number | UN1993 |
| UN proper shipping name | FLAMMABLE LIQUIDS, N.O.S. (METHYL ALCOHOL, XYLENE (ALL ISOMERS)) |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Label(s) | 3 |
| Packing group | II |
| Environmental hazards | No. |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Other information | |
| Passenger and cargo aircraft | Forbidden. |
| Cargo aircraft only | Forbidden. |

IMDG

<Unspecified>

| | |
|------------------------------|---|
| UN number | UN1993 |
| UN proper shipping name | FLAMMABLE LIQUIDS, N.O.S. (METHYL ALCOHOL, XYLENE (ALL ISOMERS)) |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Label(s) | 3 |
| Packing group | II |
| Environmental hazards | |
| Marine pollutant | No. |
| EmS | Not available. |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not established.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

| | |
|-----------------------------|---------|
| ETHYLBENZENE (CAS 100-41-4) | Listed. |
| METHANOL (CAS 67-56-1) | Listed. |
| TOLUENE (CAS 108-88-3) | Listed. |
| XYLENE (CAS 1330-20-7) | Listed. |

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

| | |
|--------------------------|------------------------|
| Hazard categories | Immediate Hazard - Yes |
| | Delayed Hazard - Yes |
| | Fire Hazard - Yes |
| | Pressure Hazard - No |
| | Reactivity Hazard - No |

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No**SARA 313 (TRI reporting)**

| Chemical name | CAS number | % by wt. |
|---------------|------------|-----------|
| XYLENE | 1330-20-7 | 50 - < 60 |
| METHANOL | 67-56-1 | 30 - < 40 |
| ETHYLBENZENE | 100-41-4 | 10 - < 20 |
| TOLUENE | 108-88-3 | < 1 |

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

ETHYLBENZENE (CAS 100-41-4)
 METHANOL (CAS 67-56-1)
 TOLUENE (CAS 108-88-3)
 XYLENE (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

TOLUENE (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

TOLUENE (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

TOLUENE (CAS 108-88-3) 594

US state regulations**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

US. Massachusetts RTK - Substance List

ETHYLBENZENE (CAS 100-41-4)
 METHANOL (CAS 67-56-1)
 TOLUENE (CAS 108-88-3)
 XYLENE (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

ETHYLBENZENE (CAS 100-41-4)
 METHANOL (CAS 67-56-1)
 TOLUENE (CAS 108-88-3)
 XYLENE (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

ETHYLBENZENE (CAS 100-41-4)
 METHANOL (CAS 67-56-1)
 TOLUENE (CAS 108-88-3)

XYLENE (CAS 1330-20-7)

US. Rhode Island RTK

ETHYLBENZENE (CAS 100-41-4)

METHANOL (CAS 67-56-1)

TOLUENE (CAS 108-88-3)

XYLENE (CAS 1330-20-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

International Inventories

All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

16. Other information, including date of preparation or last revision

Issue date 05-20-2015

Version # 01

HMIS® ratings Health: 2
Flammability: 3
Physical hazard: 0

NFPA ratings Health: 2
Flammability: 3
Instability: 0

Preparation Information and Disclaimer

This document was prepared by FCSD-Toxicology, Ford Motor Company, Diagnostic Service Center II, 1800 Fairlane Drive, Allen Park, MI 48101, USA, based in part on information provided by the manufacturer. The information on this data sheet represents our current data and is accurate to the best of our knowledge as to the proper handling of this product under normal conditions and in accordance with the application specified on the packaging and/or technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user. To the extent that there are any differences between this product's Safety Data Sheet (SDS) and the consumer packaged product labels, the SDS should be followed.

Part number(s) PM-4HVC-D